

Product Data Sheet

	HARDWARE Access Terminal: <i>Width:</i> 110 mm / 4.3 inches, <i>Height:</i> 28 mm / 1.1 inches, <i>Depth:</i> 65 mm / 2.6 inches PCI Card: Low profile PCI plug-in card (includes standard and low profile PCI bracket)
Size	
Power Supply	No external power adapters are required Power to the access terminals is provided by the PCI card through the cable
LED Indicator	<i>Power/Connection:</i> Green LED located on front of access terminal
Peripheral Connections	 1 SPEAKER 2 PS/2 KEYBOARD 3 PS/2 MOUSE 4 VIDEO OUTPUT 5 ETHERNET
Connection to Host PC	Standard Category 5 or 5e UTP cable: up to 5 meters (16 feet) Standard Category 6 STP cable: up to 7 meters (23 feet)
Video Resolution**	800x600 and 1024x768, 16-bit color maximum, 60 Hz refresh rate
Audio	Stereo output via speaker port
Data Security	No USB ports on terminal ensure absolute data security USB ports on host PC can be assigned to different users Note: Local user access to USB ports requires separate USB extension cables -- not included
Reliability (MTBF)	>100,000 hours (calculated using Bellcore Issue 6 TR-332, Case 2, Part I at 40°C)
Certifications	FCC Class B, CE, MIC, and RoHS
	TERMINAL SERVICES SOFTWARE 30 users* when using a server host OS (i.e. Windows Server 2003) 10 users when using a desktop OS (i.e. Windows XP) NAccess terminal services software with User eXtension Protocol (UXP) Microsoft: Windows XP Professional and Media Center Edition 2005 Windows Server 2003, Small Business Server 2003 Linux: several variants (refer to support section of Website for latest supported revisions of Linux) Online remote update via NAccess Management Console (included)
Max # Users Per PC	
User Software	
Supported Operating Systems	
Maintenance	
	SYSTEM REQUIREMENTS AND OPTIONS See Recommended Host Configuration Guide at: http://www.ncomputing.com/ncomputing/support/download.php X300 Kit includes access terminal, power supply/cord, software installation & user's guide CD/license, Quick Install Guide, monitor mounting bracket and LAN cable. PC, monitor, PS/2 keyboard, PS/2 mouse, speakers and other peripherals are NOT included and must be purchased separately. NControl (remote control and management), NShield (hard drive partition recovery)
Host PC Configuration	
Kit Contents	
Optional Software	

* The number of users and individual host will support depends upon the host system capabilities as well as the applications used and performance expectations for those applications. It is recommended that new customers test their application(s) before adding additional users.

** Does not support 3D games or full screen home theater applications.

*** Application software and OS licenses for the host PC and X300 may be required by the respective software vendor and must be purchased separately.

www.ncomputing.com

© Copyright 2003-2007, NComputing, Inc. All rights reserved. NComputing is the property of NComputing. Other trademarks and trade names are the property of their respective owners. Specifications subject to change without notice. Depending on the host computers configuration application performance may vary.

X300 11.05.07